

MARTIN F WEBER CO -- 1681 TURPENOID -- 6850-00F036205

===== Product Identification =====

Product ID:1681 TURPENOID
MSDS Date:08/01/1995
FSC:6850
NIIN:00F036205
=== Responsible Party ===
Company Name:MARTIN F WEBER CO
Address:2727 SOUTHAMPTON RD
City:PHILADELPHIA
State:PA
ZIP:19154-1293
Country:US
Info Phone Num:215-677-5600
Emergency Phone Num:215-677-5600
CAGE:MART5
=== Contractor Identification ===
Company Name:MARTIN F WEBER CO
Address:2727 SOUTHAMPTON RD
Box:City:PHILADELPHIA
State:PA
ZIP:19154-1293
Country:US
Phone:215-677-5600
CAGE:MART5

===== Composition/Information on Ingredients =====

Ingred Name:STODDARD SOLVENT (PETROLEUM DISTILLATE), MINERAL SPIRITS
98-2
CAS:8052-41-3
RTECS #:WJ8925000
Fraction by Wt: 100%
Other REC Limits:525 MG/CUM
OSHA PEL:500 PPM
ACGIH TLV:100 PPM

===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:NO Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:INGESTION: MAY BE HARMFUL/FATAL.
INHALATION: HARMFUL. EYES: IRRITATION.
Explanation of Carcinogenicity:NONE
Effects of Overexposure:IRRITATION, NAUSEA, HEADACHE, CONFUSION,
INSTABILITY.

===== First Aid Measures =====

First Aid:INGESTION: DON'T INDUCE VOMITING. INHALATION: REMOVE TO FRESH
AIR. OBTAIN MEDICAL ATTENTION IN ALL CASES.

===== Fire Fighting Measures =====

Flash Point:120-130F
Lower Limits:0.7
Upper Limits:5

Extinguishing Media: DRY CHEMICAL, FOAM, CO2.

Unusual Fire/Explosion Hazard: COMBUSTIBLE.

===== Accidental Release Measures =====

Spill Release Procedures: KEEP SOURCES OF IGNITION AWAY. SMALL AMOUNTS MAY BE CLEANED UP W/RAGS/PAPER TOWELS & TRANSFERRED TO AIRTIGHT CONTAINERS FOR DISPOSAL.

===== Handling and Storage =====

Handling and Storage Precautions: DON'T USE NEAR HEAT/FLAME.

Other Precautions: AVOID PROLONGED CONTACT W/SKIN. KEEP OUT OF REACH OF CHILDREN.

===== Exposure Controls/Personal Protection =====

Respiratory Protection: NOT REQUIRED IF ROOM IS ADEQUATELY VENTILATED.

Ventilation: LOCAL EXHAUST: USE EXHAUST FAN ALONG W/FRESH AIR SOURCE TO AVOID VAPOR BUILDUP.

Protective Gloves: RUBBER

Eye Protection: RECOMMENDED

Work Hygienic Practices: WASH HANDS AFTER USE. DON'T SMOKE WHILE USING.

Supplemental Safety and Health

===== Physical/Chemical Properties =====

Boiling Pt: B.P. Text: 340-400F

Vapor Pres: 2

Vapor Density: 4.9

Spec Gravity: 0.759

Evaporation Rate & Reference: (ETHER = 1): 70

Solubility in Water: <5%

Appearance and Odor: CLEAR ODORLESS LIQUID

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid: YES

STRONG OXIDIZING AGENTS.

Stability Condition to Avoid: HEAT, FLAME.

Hazardous Decomposition Products: CO, CO2.

===== Disposal Considerations =====

Waste Disposal Methods: DISPOSE OF IAW/FEDERAL, STATE & LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.