3625

9724865-66-67

MATERIAL SAFETY DATA SHEET

NASCO ARTIST QUALITYACRYLIC POLYMER MEDIUM

ROCK PAINT DISTRIBUTING CORP.
MANUFACTURER

MSDS NUMBER

365 SUNNYSIDE DR. P.O. BOX 482
ADDRESS

CAS NUMBER

MILTON, WI 53563

JANUARY 2006
DATE PREPARED

(608)868-6873 (920) 563-8545
PHONE NUMBER(FOR INFORMATION)

PREPARED BY

SECTION 1 - MATERIAL IDENTIFICATION AND INFORMATION

COMPONENTS: CHEMICAL NAME & COMMON NAMES	%	OSHA PEL	ACGIH TLV	OTHER LIMITS RECOMMENDED
WATER				
ACRYLIC EMULSION				
CALCIUM CARBONATE				
PROPYLENE GLYCOL				
CELLULOSIC				

AS PER ASTM D-4236 AND AS PER THE ART AND CRAFT MATERIALS INSTITUTE (ACMI) INC. THIS PAINT HAS BEEN CERTIFIED NON-TOXIC.

SECTION 2 - PHYSICAL/CHEMICAL CHARACTERISTICS

BOILING POINT - ABOUT 212

SPECIFIC GRAVITY (H2O=1) - ABOUT 9LBS PER GAL

VAPOR PRESSURE (mm Hg & TEMPERATURE) - 17mm Hg

MELTING POINT - N/A

VAPOR DENSITY (AIR=1) - NOT AVAILABLE

EVAPORATION RATE (WATER=1) - SLOWER

SOLUBILITY IN WATER - DILUTABLE

WATER REACTIVE - N/A

APPEARANCE & ODOR - SLIGHT AMMONIA ODOR, OR NO ODOR PRESENT

SECTION 3 - FIRE AND EXPLOSION HAZARD DATA

FLASH POINT & METHOD USED: N/A

AUTO IGNITION TEMPERATURE: N/A

FLAMMABILITY LIMITS IN AIR % BY VOLUME: N/A

LEL

UEL

EXTINGUISHER MEDIA

FOAM - DRY CHEMICAL - CO2 - WATER SPRAY OR FOG

SPECIAL FIRE FIGHTING PROCEDURES

N/A

UNUSUAL FIRE AND EXPLOSION HAZARDS

N/A

SECTION 4 - REACTIVITY HAZARD DATA

ARTIST QUALITY POLYMER -2

STABILITY
[X] STABLE
[ ] UNSTABLE

CONDITIONS TO AVOID
NONE KNOWN

INCOMPATABILITY (MATERIALS TO AVOID) NONE KNOWN-HOWEVER PRODUCT PROPERTIES MAY BE ALTERED BY MIXING WITH SOME MATERIALS.

HAZARDOUS DECOMPOSITION PRODUCTS THERMAL DECOMPOSITION IN THE PRESENCE OF AIR MAY YIELD CARBON MONOXIDE AND/OR CARBON DIOXIDE AND TRACES OF MONOMER.

HAZARDOUS POLYMERIZATION
[ ] MAY OCCUR
[X] WILL NOT OCCUR

CONDITIONS TO AVOID

SECTION 5 - HEALTH HAZARD DATA

PRIMARY ROUTES OF ENTRY
[ ] INHALATION [ ] INGESTION
[ ] SKIN ABSORTION [X] NOT HAZARDOUS

CARCINOGEN LISTED IN
[ ] NTP [ ] OSHA
[ ] IARC MONOGRAPH [ ] NOT LISTED

HEALTH HAZARDS
ACUTE
CHRONIC

SIGNS AND SYMPTOMS

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE

EMERGENY FIRST AID PROCEDURES -

SEEK MEDICAL ASSISTANCE FOR FURHTER TREATMENT, OBSERVATION AND SUPPORT IS NECESSARY.

EYE CONTACT - DIRECT CONTACT WITH EMULSION MAY RESULT IN IRRITATION. FLUSH EYES IMMEDIATELY WITH PLENTY OF WATER FOR AT LEAST 15 MINUTES AND CONSULT A PHYSICIAN. REMOVE CONTACTS FROM VICTIM.

SKIN CONTACT - PROLONGED OR REPEATED CONTACT WITH EMULSION MAY CAUSE SOME SKIN IRRITATION. WASH SKIN THOROUGHLY WITH SOAP AND WATER; IF DRENCHED REMOVE AND WASH CLOTHING BEFORE REUSE.

INHALATION - N/A

INGESTION - IF VICTIM IS CONSCIOUS, GIVE TWO GLASSES OF WATER TO DRINK AND CALL A PHYSICIAN.

SECTION 6 - CONTROL AND PROTECTIVE MEASURES

RESPIRATORY PROTECTION (SPECIFY TYPE) -

PROTECTIVE GLOVES - RUBBER GLOVES RECOMMENDED

EYE PROTECTION - CHEMICAL GOGGLES WITH EYE GUARD

VENTILATION TO BE USED - LOCAL EXHAUSE - MECHANICAL (GENERAL) - SPECIAL -
OTHER (SPECIFY) -

OTHER PROTECTIVE CLOTHING AND EQUIPMENT - N/A

HYGIENIC WORK PRACTICES -

SECTION 7 - PRECAUTIONS FOR SAFE HANDLING AND USE/LEAK PROCEDURES

STEPS TO BE TAKEN IS MATERIAL IS SPILLED OR RELEASED -
ABSORB WITH DRYING MATERIAL OR FLUSH SPILLED MATERIAL INTO SUITABLE RETAINING AREA OR CONTAINER. PREVENT SPILLED LIQUID FROM ENTERING SEWERS, STORM DRAINS, DRAINAGE SYSTEMS AND NATURAL WATERWAYS.

WASTE DISPOSAL METHODS -
DISPOSE OF PRODUCT IN ACCORDANCE WITH APPLICABLE LOCAL, COUNTY, STATE AND FEDERAL REGULATIONS.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE
SHOULD BE STORED AT ROOM TEMPERATURE TO PROLONG SHELF LIFE.
KEEP FROM FREEZING AND FROM EXCESSIVE HEAT.

OTHER PRECAUTIONS AND/OR SPECIAL HAZARDS -
N/A

HIMS RATING HEALTH 1 FLAMMABILITY 0 REACTIVITY 0 PERSONAL PROTECTION A